



CE DECLARATION OF PERFORMANCE
No. CES520150401KL

1.- Identification code of the product type and any other element allowing identification of the product:

Dry-pressed ceramic tiles with water absorption $E_v \leq 0.5\%$ for internal and external walls and floors with antislip properties.

2.- Intended use:

Internal and external walls and floors with antislip properties

3.- Name or registered mark and address of the manufacturer

KTL

KTL Cerámicas SLU

C/ del Ferrocarril 4 12593-Moncofa (Castellón) ESPAÑA

4.- System of assessment and verification of constancy of performance (AVCP)

System 4

5.- Name and identification number of notified laboratory, if relevant:

Not relevant

6.- Declared Performances:

SERIE 5		
Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	Class A1-A1 _{FL}	EN 14411:2012
Release of dangerous substance for: <ul style="list-style-type: none">- Cadmium- Lead	NPD NPD	
Breaking Strength	≥ 1300 N	
Slipperiness PTV (wet), slider 57, EN16165:2021 Annex C	>35	
Adhesion strength Cementitious adhesive type C2	≥ 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for: <ul style="list-style-type: none">- Internal Use- External use	Pass Pass	

The performance of the product identified previously is in conformity with the declared performance, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer indicated above.

Nules, a 11/12/2023

Signature:

KTL CERAMICAS S.L.U.
CIF. B-01771815
Calle del Ferrocarril, 4
12593 Moncofa (Castellón) Spain
Tel. +34 964 584 069 - Fax +34 964 584 070